



# CHASSIS

- Axles..... 113
- Brakes ..... 115
- Hubs, Drums, Discs..... 116
- Mudguards & Wheel Equipment ..... 117
- Jockey Wheels ..... 118
- Jockey Wheels Spare Parts..... 121
- Corner Steadies ..... 121
- Couplings ..... 123
- Springs..... 126
- Vehicle Steps ..... 128
- Caravan Movers..... 129

## AXLES



### SUIT HOLDEN BEARINGS 40MM SQUARE 1000KG EACH

- 036015 1397MM LM MACHINED PROFILE
- 036022 1600MM LM MACHINED PROFILE
- 036024 1650MM LM MACHINED PROFILE
- 036026 1702MM LM MACHINED PROFILE
- 036027 1727MM LM MACHINED PROFILE
- 036031 1829MM LM MACHINED PROFILE
- 036032 1854MM LM MACHINED PROFILE
- 036036 1956MM LM MACHINED PROFILE
- 036039 2032MM LM MACHINED PROFILE
- 036045 2184MM LM MACHINED PROFILE
- 036051 2337MM LM MACHINED PROFILE
- 036055 2438MM LM MACHINED PROFILE



### SUIT FORD (SLIMLINE) BEARINGS 45MM SQUARE 1450KG EACH

- 036067 1905MM SLIMLINE MACHINED PROFILE
- 036069 1980MM SLIMLINE MACHINED PROFILE
- 036071 2108MM SLIMLINE MACHINED PROFILE
- 036072 2185MM SLIMLINE MACHINED PROFILE
- 036074 2260MM SLIMLINE MACHINED PROFILE
- 036076 2362MM SLIMLINE MACHINED PROFILE
- 036077 2440MM SLIMLINE MACHINED PROFILE



### STUB AXLES SUIT HOLDEN BEARINGS

- 036079 40MM ROUND 250MM O/A
- 036084 40MM SQUARE 200MM O/A
- 036085 40MM SQUARE 250MM O/A

### STUB AXLES SUIT FORD (SLIMLINE) BEARINGS

- 036083 45MM ROUND 280MM O/A
- 036086 45MM SQUARE 305MM O/A



**AXLE FLAT WASHER 3/4IDX1&1/2**

006550



**AXLE NUT PIN & WASHER KIT**

050195



**AXLE NUT/PIN/WASHER SKIN PAK X2**

050108



**DUST CAP METAL SUIT 1.5/2T AXLE, 2 1/2IN**

006569



**OIL SEAL HOLDEN DOUBLE LIP STUB AXLE (2.328" X 1.437" X 0.4")**

006558

Oil Seal 609 Suit Standard Bearing. These fit the HT holden bearings, when used on a standard axle.



**OIL SEAL 2 TONNE**

038134

AL-KO Oil Seal 494015, Suit heavy duty axles with 2 tonne and 3 tonne capacity.



**OIL SEAL SLIMLINE**

006559

Oil Seal 610 Suit slimline Bearing, Slimline seal suits heavy duty axle with Ford bearings.

## BEARINGS



**ON ROAD BEARING KITS**

(Inner bearing, outer bearing, grease seal, grease cap)

- 036183 LM HOLDEN CHINA
- 006563 LM HOLDEN JAPAN
- 051353 LM HOLDEN CHINA ARK
- 050118 S/L (FORD) CHINA
- 006565 S/L (FORD) JAPAN
- 006562 COMPOSITE JAPAN
- 006560 PARALLEL JAPAN
- 050127 2 TONNE JAPAN



**MARINE BEARING KITS WITH MARINE SEAL**

(Inner bearing, outer bearing, grease seal, grease cap)

- 050117 LM HOLDEN CHINA
- 050119 LM HOLDEN JAPAN
- 051348 LM HOLDEN CHINA ARK
- 050125 S/L (FORD) CHINA



**OUTER BEARING**

050276 USA BEARING

**FEATURES**

- L44649
- Often used as the outer bearing on imported USA boat trailers



**H26 GREASE CAPS X 2 SKIN PACK**

050136

- Housing diameter: 45.2mm
- Suits LM & SL Bearing Hubs/Drums
- Genuine Alko replacement part



**LUBRIMATIC MARINE GREASE**

006576

Recommended for use on all boat trailers.



**HIGH TEMP BEARING GREASE 500G**

006579

# BRAKES



## BRAKE PLATES AND SPARE PARTS

- 006340 BRAKE ASSY PLATE RIGHT HAND, MECHANICAL 9"
- 006341 BRAKE ASSY PLATE LEFT HAND, MECHANICAL 9"
- 036113 BRAKE ASSY PLATE 250X56 ELECTRICAL, TRAILTECH RIGHT HAND
- 036114 BRAKE ASSY PLATE 250X56 ELECTRICAL, TRAILTECH LEFT HAND
- 006333 BRAKE ASSY PLATE RIGHT HAND AL-KO
- 006334 BRAKE ASSY PLATE LEFT HAND AL-KO
- 036112 BRAKE ASSY PLATE ELECTRICAL RIGHT HAND, OFF ROAD 10"
- 036111 BRAKE ASSY PLATE ELECTRICAL LEFT HAND, OFF ROAD 10"
- 033582 BRAKE ASSY PLATE ELECTRICAL SUIT 12" - PR LH/RH
- 034962 12" BRAKE ASSY PLATE RIGHT HAND OFF ROAD
- 006336 ADAPTOR PLATE MOUNT NUT ONLY 7/16" UNF
- 006395 ADAPTOR PLATE SUIT 40MM RND HOLE, FOR ELECT/MECH BACKING PLATE
- 006397 ADAPTOR PLATE SUIT 45MM RND HOLE, FOR ELECT/MECH

Brake assembly - Electric, LEFT, 250 x 56mm (10 Inch x 2 1/4 Inch) AL-KO, OFFROAD. They must be ordered for LEFT or RIGHT hand side of caravan / trailer. The kerb side is the LEFT side and does not include the drum which is ordered separately to match the stud pattern required.

### FEATURES

- These AL-KO OFFROAD brake assembly plates come complete with magnet and mechanical park brake lever, and brake shoes. The 4 mounting bolts are 72mm apart (centre/centre)



## HYDRAULIC BRAKE SPARE PARTS

- 034170 HYDRAULIC DISC BRAKE CALIPER AL-KO DACROMET COATED
- 036153 HYD DISC BRAKE CALIPER TRIGG A200M



## MECH DISC BRAKE PAD

- 043162 MECH BRAKE PADS ARK (PR)
- 050111 MECH BRAKE PADS AL-KO (PR)

Will also suit Trigg hydraulic calipers



## AL-KO CALIPER N/S BRAKE PAD

051123

### FEATURES

- 'Bolt On' style pad
- Suits the newer AL-KO mechanical calipers
- Sold ea



## BRAKE SHOES

- 036133 BRAKE SHOE 9"X45MM EA
- 006390 BRAKE SHOE 10"X 2 1/4" PRIMARY EA
- 006391 BRAKE SHOE 10"X 2 1/4" SECONDARY EA
- 040625 BRAKE SHOE 10" EL PR/SET SUIT 1 X WHEEL
- 034871 BRAKE SHOE 12" PRIMARY AL-KO EA
- 034872 BRAKE SHOE 12" SECONDARY AL-KO EA

Brake Shoe 230 X 45mm, Mechanical. Please NOTE: this is for a single shoe only, each wheel requires two shoes, but the leading and trailing shoes are identical for this type of brake.



## HYD DISC BRAKE PAD TROJAN AL-KO

341103

Sold Individually. 2 required per caliper



## MECHANICAL DISC BRAKE CALIPERS

- 036145 MECHANICAL DISC BRAKE CALIPER
- 036147 MECHANICAL DISC BRAKE ADAPTOR PLATE 40MM AL-KO VERSION
- 036158 MECHANICAL DISC CALIPER BOLT
- 036159 MECHANICAL DISC CALIPER RETAINING SPRING
- 036163 MECHANICAL DISC CALIPER MOUNTING BUSH



## BRAKE MAGNETS

- 006384 BRAKE MAGNET 10" SUITS HAYES AND AL-KO
- 006388 LEFT HAND OFFROAD AL-KO 10"
- 006389 RIGHT HAND OFFROAD AL-KO 10"
- 034873 BRAKE MAGNET 12IN OVAL AL-KO
- 051589 BRAKE MAGNET TO SUIT 12"
- 051590 12" OFF ROAD L/H
- 051591 12" OFF ROAD R/H

Brake Magnet, Dexter, AL-KO, Oval Type, spring & Clip. Weak or noisy brakes are often caused by uneven or excessive wear on the rubbing surface of the magnet. For balanced braking, the opposing brake magnet should be replaced at the same time. Price is for one Electric brake magnet.



## CLIP FOR KELSEY OVAL MAGNET

006385

Magnet Clip Suit Oval Type, holds the magnet onto the small centre shaft in the electric brakes.

# HUBS/DRUMS/DISCS



## HUB/DRUMS

- 042731 BOXED HUB DRUM 9" MECH FORD
- 042734 BOXED H/DRM 9" MECH FRD S/L
- 050205 BOXED H/DRUM 10" HT JAP LM
- 042712 BOXED ELECTRIC FORD 10" C/W STUDS ONLY
- 042738 BOXED ELECTRIC FORD 10" RETAIL BOXED, C/W STUDS, NUTS JAP SLIMLINE BEARINGS
- 042714 BOXED ELECTRIC LANDCRUISER 10" 6 STUD NO NUTS OR BEARINGS S/PARALLEL BEARINGS

Brake Hub Drum - Photo is representative only as numbers and position of studs vary. Price is for one side only. They fit either left or right.

- 042737 BOXED ELECTRIC LANDCRUISER 10" 6 STUD RETAIL BOXED, C/W STUDS, NUTS JAP SLIMLINE BEARINGS

Brake Hub Drum - Landcruiser 6 Stud, suit 250mm AL-KO electric brake assembly. Price is for one side only. They fit either left or right.



## WHEEL AND TYRE SPARE PARTS

- 036186 WHEEL STUD LONG SPLINE, 1/2"IND - 55MM SPEC

### SPECIFICATIONS

- Main thread is 35mm long, Thread plus spline in total is 55mm Spline outer dia is 15-15.5mm. 1/2" UNF

- 036187 WHEEL STUD SHORT SPLINE, 1/2"IND - 50MM SPEC

### SPECIFICATIONS

The combined spline and thread is 50mm The spline is 12mm long.

- 006635 WHEEL STUD SUIT 7/16"X1&5/8" HOLDEN

### SPECIFICATIONS

- Total length of spline and thread is 38mm
- Outer spline dia 13.5mm
- Outside of thread measures 11mm

- 006636 WHEEL STUD SUIT 1/2"UNFX1&5/8" FORD

- 006638 WHEEL NUT - SUIT HOLDEN 7/16"

- 006639 WHEEL NUT - SUIT FORD 1/2"



## MECHANICAL DISC BRAKES

- 036150 MECH DISC BRAKE HUB FORD BLACK
- 036166 MECH DISC BRAKE HUB HT GAL- LM BEARINGS
- 036167 MECH DISC BRAKE HUB FORD GAL - LM BEARINGS
- 036168 MECH DISC BRAKE HUB HQ GAL - LM BEARINGS
- 038754 MECHANICAL DISC BRAKE HUB HT HOLDEN BOXED GALVANISED C/W SLIMLINE BEARINGS
- 038755 MECHANICAL DISC BRAKE HUB - FORD BOXED GALVANISED C/W SLIMLINE BEARINGS



## PLATED STUD KIT

- 050131 PLATED TRAILER 7/16 NUT KIT PKT 5
- 050134 PLATED TRAILER 1/2 NUT KIT PKT 5
- 050132 PLATED 7/16 TRAILER STUD KIT PKT 5
- 050130 PLATED TRAILER STUD & NUT KIT PKT 5 (7/16")
- 050135 PLATED TRAILER STUD & NUT KIT PKT 5 (1/2")



## TRAILER STUD & NUT KIT 1/2 UNF

- 050129

### SPECIFICATIONS

- Natural finish
- Pkt of 5
- 1/2" stud & nut



- TRAILER STUD & NUT KIT 7/16 UNF
- 050128
- Specifications
- Natural finish
- Pkt of 5
- 7/16" stud & nut



## HUB KITS - GALVANISED

- 050197 NON BRAKED HUB HT (SMALL FLANGED) GALV SUIT O/S 9" ALLOY WHEELS - LM BEARINGS
- 036102 NON BRAKED HUB HT GALV - LM BEARINGS
- 040629 HUB KIT GAL HT CH S/L BEARING
- 042727 NONBRAKED HUB FORD GALV - LM BEARINGS
- 050206 NON BRAKED HIB FORD GALV - S/L (FORD) BEARINGS

Non Braked Hub - HT Holden, galvanised. Includes cones, bearings, seal and cap.

### SPECIFICATIONS

- Non-braked hub including 5 studs
- 5 wheel nuts
- 1 x Outer Cone/ Bearing
- 1 x Cup
- 1 x Inner Cone/ Bearing
- 1 x Cup
- 1 x 28550 Rear Grease Seal
- 1 x DC1 Grease Cap



## NON BRAKED HUBS NATURAL FINISH

- 036088 MINI HOLDEN BEARINGS - 4 STUD
- 038751 HQ LM (HOLDEN) BEARINGS
- 051347 FORD LM (HOLDEN) BEARINGS - ARK
- 042720 FORD LM HOLDEN BEARINGS
- 036101 SUIT LANDCRUISER 6 STUD C/W STUDS NUTS AND HOLDEN LM BEARINGS
- 036096 NON BRAKED HUB SUIT FORD S/L
- 050196 L/C S/L LANDCRUISER S/L (FORD) BEARINGS

# MUDGUARDS & WHEEL EQUIPMENT



## WHEEL ARCH

006543 WHEEL ARCH 30IN S6L GALV

006544 WHEEL ARCH TANDEM GALV



## MUD GUARD - POLY PLASTIC

Strong with steps on both sides as well as on top. Mud flaps, brackets not included.

036283 MUDGUARD POLY SMALL 10" WHITE

036284 MUDGUARD POLY SMALL 10" SILVER

036285 MUDGUARD POLY MED 13" WHITE

036286 MUDGUARD POLY MED 13" SILVER

036287 MUDGUARD POLY LARGE 14" WHITE

036288 MUDGUARD POLY LARGE 14" SILVER

043662 MUDGUARD BRACKET 23.5 X 7.5

051398 MUDGUARD POLY SMALL 10" BLACK

051399 MUDGUARD POLY MED 13" BLACK

051400 MUDGUARD POLY LARGE 14" BLACK



## ALLOY WHEEL (VELOX)

036470 HUB MOUNT WITH TYRE 10"

036462 BEARING MOUNT WITH TYRE 8"



## WHEELS

036455 STEEL ROAD WHEEL, SUIT HOLDEN HT14" SUNRAYSLA BLACK

Sunraysia Black wheel rim, HT Holden, 14" x 6". These black painted sunraysia steel rims suit the HT stud pattern.

### SPECIFICATIONS

- Material: Painted steel rims
- Size: 14 inch dia, 6 inch wide
- Suit: Holden HT, HG, HK
- PCD: 4 1/4 inch (107.95mm)
- Adjacent Studs: 2 1/2 inches (63.45mm) between centres.
- Suit Studs: 5 x 7/16 inch.
- Colour: Black

006615 STEEL ROAD WHEEL, SUIT FORD 14" X 6" SUNRAYSLA WHITE

Sunraysia White Road Wheel Ford, 14 Inch x 6 inch. This steel rim suits the ford stud pattern and is a popular replacement for the standard rims.

### SPECIFICATIONS

- Material: Painted steel rims
- Size: 14 inch dia, 6 inch wide
- Suit: Ford
- PCD: 4 1/2 inch (114.30mm)
- Adjacent Studs: 2 5/8 inches (67.18mm) between centres
- Suit Studs: 5 x 1/2 inch
- Colour: White

038357 STEEL ROAD WHEEL, SUIT HOLDEN HR 330MM BLACK

036452 STEEL ROAD WHEEL, SUIT HOLDEN HQ 355MM BLACK

Steel Road wheel rim, HQ Holden, 14 x 6 inch. These black painted steel suit the HQ stub pattern.

### SPECIFICATIONS

- Material: Painted steel rims
- Size: 14 inch dia, 5.5 inch wide
- THESE ARE NOT SUITABLE FOR YOUR HOLDEN!
- PCD: 4 3/4 inch (120.65mm)
- Colour: Black

043161 13" WHITE POWDER COATED WHEEL TO SUIT FORD WITH 155/80 TYRE RATED AT 437KG

043160 GALVANIZED 13" WHEEL WITH ALL TERRAIN TREAD FOR HT/FORD 165R13C TYRE (MULTI FIT) RATED AT 670KG



## MULTI-FIT SPARE WHEEL CARRIER

051361

### SPECIFICATIONS

- Suits 4,5 & 6 stud wheels
- Suits drawbar size 50-100mm
- Locking facility secures wheel and prevent theft

000512 SPARE WHEEL MOUNT BOLT ON - STRAIGHT

Spare Wheel Carrier Bolt On. The flat base includes 2 x 125mm u-bolts which cover up to 100mm of bumper thickness. If using on an A-frame the wheel will be inline or at 90 degrees to the A-Frame. These are not recommended for LARGE 4WD wheels.

### SPECIFICATIONS

- The upright is 395mm from the bumper top, to the centreline of the wheel mount
- The Wheel backing plate is 160mm offset from the centreline of the upright. It has 20mm centre mounting bolt with provision to accept a padlock single locating pin that fits thru one wheel stud hole (any stud pattern).
- The steel profile is 65mm x 35mm.



000512



# JOCKEY WHEELS



## SWIVEL JOCKEY WHEELS WITH SMALL CLAMP S/50 X 50 FRAME BOLT OR WELD ON

036244 6" WHEEL  
006416 8" WHEEL

### FEATURES

- Swivel bracket allows the jockey wheel to stay permanently attached.
- No need to remove for storage
- Simple swing away action for travelling position
- Angle tube prevents rotation when stowed
- Large heavy duty wheel for easy maneuvering on soft or uneven surfaces
- Zinc coated for lasting protection

### 8" SPECIFICATIONS

- Static Capacity: 400kg
- Wheel Size: 200mm (8") solid tyre
- Weight: 8.5kg
- Max Lift / extension: 250mm
- Minimum Ground Clearance(G1): 310mm (from centre of drawbar)
- Maximum Ground Clearance(G2): 560mm (from centre of drawbar)
- Overall Shaft Height Open: 820mm
- Overall Shaft Height Closed: 570mm
- Finish: Zinc Plated
- Clamp: Small Swivel Bracket - Bolt on (u-bolts or bolts not included)



## JOCKEY STANDS - VARIOUS

039992 ARK ADJUSTABLE STAND WITH SWIVEL BRACKET - SIDE WINDER

006445 EASYLIFT ADJ STAND NO CLAMP 27"

006450 AL-KO ADJUSTABLE STAND AND CLAMP 14"

Adjustable jockey stand with flat base. These come with the clamp as shown.

### SPECIFICATIONS

- Outside tube is 355mm.
- Maximum lift from ground is 500mm

006451 AL-KO ADJUSTABLE STAND AND CLAMP 20"

- Adjustable jockey stand with flat base and clamp. Outside tube is 510mm.

### SPECIFICATIONS

- Zinc Coated
- Outside tube is 510mm
- Extends 240mm
- 50mm dia clamp supplied

## JOCKEY WHEEL W/CLAMP OR NO CLAMP

006402 JOCKEY WHEEL 6X2IN STD W/CLAMP FEATURES

- Included AL-KO Standard Clamp - this can be bolted or welded on. (Bolts not included)
- Zinc coated for lasting protection

### SPECIFICATIONS

- Static Capacity: 400kg. Weight: 5.5kg
- Wheel Size: 150mm (6") solid tyre
- Max Lift / extension: 265mm
- Minimum Ground Clearance(G1): 202mm (from centre of drawbar)
- Maximum Ground Clearance(G2): 649mm (from centre of drawbar)
- Overall Shaft Height Open: 772mm
- Overall Shaft Height Closed: 507mm
- Finish: Zinc Plated
- Clamp: Standard bolt/weld on (bolts not included)



006404 JOCKEY WHEEL 6X2" STD NO CLAMP

006408 JOCKEY WHEEL 8X2 W/STD CLAMP

### FEATURES

- Large heavy duty wheel for easy maneuvering on soft or uneven surfaces
- Included AL-KO Standard Clamp - this can be bolted or welded on. (Bolts not included)
- Zinc coated for lasting protection

### SPECIFICATIONS

- Static Capacity: 400kg. Weight: 7kg
- Wheel Size: 200mm (8") solid tyre
- Max Lift / extension: 265mm
- Minimum Ground Clearance(G1): 262mm (from centre of drawbar)
- Maximum Ground Clearance(G2): 697mm (from centre of drawbar)
- Overall Shaft Height Open: 832mm
- Overall Shaft Height Closed: 567mm
- Finish: Zinc Plated
- Clamp: Standard bolt/weld on (bolts not included)

038556 AL-KO STANDARD WITH CLAMP 350MM X 410MM

Wide, solid rubber wheel for easy maneuvering. Includes Sto clamp

042352 AL-KO EXTRA HEIGHT NO CLAMP 8" 200MM

### FEATURES

- Large heavy duty wheel for easy maneuvering on soft or uneven surfaces
- Extra height great of off road caravans and camper trailers
- Zinc coated for lasting protection

### SPECIFICATIONS

- Static Capacity: 400kg. Weight: 7kg
- Wheel Size: 200mm (8") solid tyre
- Max Lift / Extension: 265mm
- Minimum Ground Clearance(G1): 370mm (from centre of drawbar)
- Maximum Ground Clearance(G2): 767mm (from centre of drawbar)
- Overall Height Open: 995mm
- Overall Height Closed: 730mm
- Finish: Zinc Plated
- Clamp: None Supplied - see related items below for Standard or Wide Clamps



## SWIVEL JOCKEY WHEELS WITH LARGE CLAMP

006406 JOCKEY WHEEL 6IN W LGE SWIVEL  
006410 JOCKEY WHEEL 8IN W LGE SWIVEL  
038561 JOCKEY WHEEL 350X410MM W/ SWIV

Attached swivel clamp can be bolted to 50/75/100mm drawbars.



## ARK JOCKEY WHEELS

044987 ARK SPARE HANDLE

051340 ARK 8" JOCKEY WHEEL

051341 ARK 10" JOCKEY WHEEL

051342 ARK 10" JOCKEY WHEEL

051343 ARK 6" JOCKEY WHEEL

051344 ARK 8" JOCKEY WHEEL PREMIUM

051346 ARK 8" JOCKEY WHEEL

051358 ARK 6" ECONOMY JOCKEY WHEEL

051362 ARK 10" JOCKEY WHEEL

051363 ARK 10" JOCKEY WHEEL

051339 ARK 6" JOCKEY WHEEL

051351 ARK EZIMOVER JOCKEY WHEEL

051356 ARK 6" JOCKEY WHEEL

051366 ARK 8" JOCKEY WHEEL HEAVY DUTY

051368 ARK JOCKEY STAND 350KG

051369 ARK JOCKEY STAND 350KG

051360 ARK 6" JOCKEY WHEEL PREMIUM

051370 ARK 8" JOCKEY WHEEL



## JOCKEY WHEEL TWIN WHEEL HEAVY DUTY WITH SOLID WHEELS, INC CLAMP LOAD CAPACITY 1000KG

042292



## TRAIL-A-MATE HYDRAULIC JOCKEY WHEEL AND JACK

### 000417 TRAIL-A-MATE JOCKEY WHEEL, HYDRAULIC, LIFTING CAPACITY 1000KG

A hydraulic jockey wheel that converts in to a jack when you need it. You simply swap the wheel for a solid base plate. The key features of the Trail-A-Mate are as follows:

- Capacity - WLL 1,000kg / ATM 2,900kg
- Versatility - Easily converts from a jockey wheel to a jack
- Ease of Use - Being hydraulic it takes very little effort to operate
- Safety - Fully complies with the Australian mandatory safety standards (2693:2007) It has many applications and uses such as caravanning, horse floats, trailers, food vans, motorhomes.

#### FEATURES

- For stress free raising and lowering of caravans, boats and trailers
- Safety nonslip lugs built in
- No need to climb under the vehicle to jack it up
- Suitable for most jockey wheel brackets
- Both a jack and jockey wheel
- Trail-A-Mate - safe working load of 1000kg when base is fitted
- Trail-A-Mate II - safe working load of 1500kg when base is fitted

### 040981 TRAIL-A-MATE MKII JACK, HYDRAULIC, LIFTING CAP 1500KG NO WHEEL (JACK ONLY)

Trail-A-Mate MkII is a hydraulic caravan jack designed to lift larger and heavier caravans than the original Trail-A-Mate Jockey Wheel/Jack. The outside diameter is 60mm. There is an optional 60mm A-Frame clamp

#### FEATURES

- Requires 60mm clamp to be purchased separately if used on the A-Frame.
- Does NOT fit standard 50mm clamp
- Easy to Use - Being hydraulic it takes very little effort to operate
- Safety - Fully complies with the Australian mandatory safety standards (2693:2007)

#### SPECIFICATIONS

- Capacity: 1500kg /ATM 3500kg
- Comes with detachable flat base.
- Comes with jacking clamp as per the photo above.

### 000418 TRAIL-A-MATE BASE PLATE

### 000420 TRAIL-A-MATE LIFTING CLAMP

### 000422 TRAIL-A-MATE JACK BRACKET ONLY

### 000427 TRAIL-A-MATE SERVICE KIT

### 000429 TRAIL-A-MATE JACK HANDLE ONLY

### 042460 TRAIL-A-MATE CLAMP 60MM

### 043244 TRAIL-A-MATE SERVICE KIT FOR MKII

### 044976 TRAIL-A-MATE WHEEL

### 050264 TRAIL-A-MATE LOCK

### 051442 TRAIL A MATE COVER



## JOCKEY WHEEL CLAMP

### 050278

AL-KO premium extra wide clamp for extra stability and strength.



## LARGE JOCKEY WHEEL HOLDER

### 050029

#### SPECIFICATIONS

- Size: 204 x 204 x 35mm
- Can be pegged to the ground suits 6", 8" and 10" jockey wheels
- Stops the jockey wheel sinking into soft ground



## JOCKEY WHEEL SIDE WIND & WIDE CLAMP

### 050151

This jockey wheel is part of the premium range and comes with a side-winder which allows for unrestricted movement, top-wind units can be obstructed by items mounted on your drawbar. This is a jockey wheel is perfect for a huge range of applications as this jockey wheel has 4 clamping positions and has an integrated gearbox that provides an effortless winding with its static capacity for up to 400kg.

## ARK SPARE JOCKEY WHEEL ONLY

### 051297

Powder coated solid rubber wheel. 12mm shaft size



## POWER MOVER

### 000464 POWER MOVER HANDLE ONLY 038543 POWER MOVER WITH SOLID WHEEL (AL-KO)

A most efficient caravan mover featuring original dual pawl ratchet system. This model can be mounted on either side of the drawbar, thereby allowing maximum maneuverability. It is fitted to the normal jockey wheel bracket and can be wound up to a height of 840mm.

#### FEATURES

- Ratchet jockey wheel
- Assists the manual movement of a caravan or trailer
- Includes handle and clamp
- 250mm diam wheel



## JOCKEY WHEEL RECEIVER RUBBER

### 000410

Jockey Wheel Receiver, Rubber. Spread the load and stop the jockey wheel rolling. This is made of strong firm rubber similar to the rubber on jockey wheels. Suits 150mm wheels

**OFF ROAD JOCKEY WHEEL**

**044576 500KG**

The Extreme Off Road Series Jockey Wheel is probably the toughest, most advanced Jockey Wheel in Australia today. But not only is it tough, it's also versatile – with multiple height options, a highly maneuverable trailing yoke design and 5 different yoke locking positions. Makes moving easy both on and off road.

**FEATURES**

- Side-winding handle
- Easier raising & lowering of trailers/caravans - away from stone guards, toolboxes or jerry can holders
- Magnetic, removable handle ensures safe stowage and prevents damage in offroad situations
- Increases load carrying capacity and eliminates the likelihood of “bend” under weight
- 4 x adjustable height positions
- 250mm height adjustability at each of the 4 positions, whilst maintaining a central swivel point for extra strength
  - Heavy duty swivel clamp
- 4 bolt pivot point ensures no more bowing under weight
- Suitable for 75mm, 100mm, 130mm and 150mm drawbars
- Comes with mounting hardware - no more welding onto drawbars
- Wheel pivots easily, even under heavy load or on soft ground
- Dual wheel with sealed bearings & offroad tread
- Increases offroad grip and spreads the load
- Variable yoke lock
- Rust resistant finish

**044577 OFF ROAD JOCKEY WHEEL 750KG**

These jockey wheels have been designed for tough Australian offroad conditions with their solid construction and 750kg rating. The versatile design includes 4 adjustable height positions, a heavy duty swivel clamp, 5 yoke locking positions, and it can be mounted on 75mm, 100mm, 130mm or 150mm drawbars. The dual wheels provide a wider footprint, spreading the load and increasing offroad grip even on soft surfaces. The trailing yoke design provides maximum maneuverability, pivoting easily even under heavy loads.

**FEATURES**

- Heavy duty swivel clamp
- 4 adjustable height positions
- Dual wheel, trailing yoke design for maximum maneuverability
- Magnetic, removable winder handle
- Multiple wheel locking positions for stowage
- Rust resistant finish

**SPECIFICATIONS**

- Static Capacity: 750kg
- Wheel Size: Dual 200mm (8”) solid tyre
- Weight: 20kg
- Max Lift / extension: 250mm
- Minimum Ground Clearance: 285mm (from centre of drawbar)
- Maximum Ground Clearance: 710mm (from centre of drawbar)
- Overall Height Open: 895mm
- Overall Height Closed: 645mm
- Finish: Zinc Plated
- Clamp: Swivel Bracket - includes mounting hardware to suit 75mm, 100mm, 130mm or 150mm drawbars

**ALSO AVAILABLE**

**051096 OFF ROAD JOCKEY WHEEL 750KG IN BLACK**





# JOCKEY WHEELS SPARE PARTS

CODE	PRODUCT NAME	036247	UBOLT KIT SUIT AL-KO J/WHEEL 75W X 75L
006429	RUBBER WHEEL AL-KO SUIT 8" X 2" X 1/2" SOLID STEEL WHEEL WITH RUBBER TYRE	006438	HANDLE ONLY FOR JOCKEY WHEEL AL-KO LOOSE
043250	CLAMP ONLY FOR JOCKEY WHEEL CAMEC	006424	PULLING HANDLE AL-KO FOR MOVING THE VAN ABOUT
050150	J/WHEEL CLAMP HANDLE SKIN PACK	036264	HANDLE ONLY JOCKEY WHEEL EASYLIFT
050144	J/WHEEL HANDLE SKIN PACK ROLL PIN STYLE	006440	THRUST BEARING JOCKEY WHEEL LOOSE
050143	J/WHEEL HANDLE SKINPACK GRUB SCREW STYLE	006425	BOLT AND WASHER KIT SUIT AL-KO 1/2" JOCKEY WHEEL CLAMP LOOSE
050149	J/WHEEL THRUST BEARING SKIN PA	006437	RUBBER TUBE ONLY SUIT 410 X 350
006418	CLAMP FOR JOCKEY WHEEL SINGLE	036266	RUBBER TYRE ONLY SUIT 4.10 X 3.50 X 4 PLY
036263	SWIVEL CLAMP NO WELD REQ AL-KO	006428	RUBBER WHEEL 6X2X1/2IN SOLID
039993	CLAMP FOR JOCKEY WHEEL BOLT-ON STYLE		
036246	UBOLT KIT SUIT AL-KO JOCKEY WHEEL 100W X 75L		

# CORNER STEADIES



## AL-KO CORNER STEADY DROP DOWN

051185

### SPECIFICATIONS

- 590mm open length
- Black finish



## AL-KO CORNER STEADY DROP DOWN

051186

### SPECIFICATIONS

- 740mm open length
- Black finish



## LEG DROP DOWN 840MM ALKO BLACK

051716

The ALKO Black 590mm Drop Down Corner Steady is designed to stabilize your trailer or caravan whilst stationary, whether the ground is hard or soft, you can rely on this corner steady for supreme stability.

### SPECIFICATIONS

- Corner steadies are not designed to be used as a jack or as the method of lifting the trailer off the ground. They are designed to stabilize the trailer or caravan when stationary.
- The Alko leg comes with a mounting plate which can be welded on.
- Winder handle not included.



## ADJUSTABLE CORNER STEADIES

Ensure the caravan or trailer is secure and even when stationary. Adjustable corner steadies are available in positive drive wind-down or dropdown models. Corner steadies are not designed as a jack and must not be used for this purpose.

### 006476 ADJUSTABLE LEG FRONT AL-KO SUIT HEX HANDLE 500MM LENGTH

AL-KO wind down legs have a solid hex nut for positive connection of winder (not included). These will extend 500mm vertically so will give an adequate range on most standard clearance caravans / trailers.

### 006457 ADJUSTABLE LEG FRONT DYMWOOD SUIT SLOTTED HANDLE 18" LENGTH

### 006469 ADJUSTABLE LEG FRONT MANUTECH SUIT HEX HANDLE 500MM LENGTH

### 006470 ADJUSTABLE LEG FRONT MANUTECH SUIT SLOTTED HANDLE 500MM LENGTH

### 006473 ADJUSTABLE LEG REAR MANUTECH SUIT SLOTTED HANDLE 500MM LENGTH

### 006477 ADJUSTABLE LEG FRONT AL-KO SUIT HEX HANDLE 600MM LENGTH

### 006478 ADJUSTABLE LEG FRONT AL-KO SUIT HEX HANDLE 700MM LENGTH

### 006479 ADJUSTABLE LEG REAR AL-KO SUIT HEX HANDLE 500MM LENGTH

### 006480 ADJUSTABLE LEG REAR AL-KO SUIT HEX HANDLE 600MM LENGTH

### 006481 ADJUSTABLE LEG GALV AL-KO SUIT HEX HANDLE 500MM TOP MOUNT - SUIT JAYCO

### 006482 ADJUSTABLE LEG GALV AL-KO SUIT HEX HANDLE 700MM TOP MOUNT - SUIT JAYCO

### 006452 RUBBER WHEEL FOR BACK LEG 3IN



### DROP DOWN CORNER STEADIES

AL-KO Hex Drive Drop Down Style Steady Zinc Plated. These stabilisers can also provide vertical support, and are therefore more rigid than the traditional angled legs. Price is for one, corner stabiliser and mounting bracket, the HEX winder handle NOT included.

These corner stabiliser drop down to any angle and are then locked in place with the quick release red handle. The winder (not included, but a socket will also do the job) is then used for the last section. The legs rotate through the full 180 degrees so they can be mounted on the left or right sides.

Each stabiliser comes with a mounting bracket that is usually welded to the chassis and the stabiliser are then bolted to this with the included bolts. It can operate on the angle at any height, just like the traditional wind down legs. Vertical height could be further extended with removable blocks.

- 006483 ADJUSTABLE LEG DROP DOWN CORNER STEADY AL-KO WITH BIG FOOT PAD SET, 590MM LENGTH EXTENDED
- 006485 ADJUSTABLE LEG DROP DOWN CORNER STEADY AL-KO WITH BIG FOOT PAD SET, 740MM LENGTH EXTENDED
- 042662 ADJUSTABLE LEG DROP DOWN CORNER STEADY AL-KO WITH BIG FOOT PAD SET, 820MM LENGTH EXTENDED
- 006488 ADJUSTABLE LEG DROP DOWN MANUTEC 415MM LENGTH
- 006489 ADJUSTABLE LEG DROP DOWN MANUTEC 455MM LENGTH
- 006490 ADJUSTABLE LEG DROP DOWN MANUTEC 515MM LENGTH
- 034280 ADJUSTABLE LEG MANUTEC WELD ON WITH LARGE ALUM FOOT 400MM LENGTH 240MM LIFT
- 042816 ADJUSTABLE LEG MANUTEC WELD ON WITH LARGE ALUM FOOT 620MM LENGTH 240MM LIFT

### ADJUSTABLE LEGS AND DROP DOWN CORNER STEADIES SPARE PARTS

CODE	PRODUCT NAME
006484	DROP DOWN CORNER STEADY RED HANDLE AL-KO, REPLACEMENT HANDLE ONLY
042054	ADJUSTABLE LEG DROP DOWN PULL PIN ASSY AL-KO TO SUIT AL-KO LEG
006486	DROP DOWN CORNER STEADY PADS AL-KO BIG FOOT SET OF 4 PROVIDES AN IDEAL FLAT LOAD BEARING SURFACE FOR SOFT GROUND
006499	CRANK HEX HANDLE 800MM AL-KO
006500	1150MM HANDLE (HEX) AL-KO HEX DRIVE
006498	JACK HANDLE DYMWOOD MILLARD OLD STYLE JACK HANDLE
006487	ADJUSTABLE LEG HANDLE SUITS MANUTEC QUICK RELEASE SWING DOWN LEG
006493	ADJUSTABLE LEG HANDLE ARTWELL SLOTTED HANDLE, 565MM OVERALL SIZE
006494	ADJUSTABLE LEG HANDLE ARTWELL SLOTTED HANDLE, 720MM OVERALL SIZE
040233	DROP DOWN CORNER STEADY PLASTIC FOOT MANUTEC PLASTIC FOOT ONLY
040234	DROP DOWN CORNER STEADY ALUMINIUM FOOT MANUTEC ALUMINIUM FOOT ONLY



### ARK DROP DOWN STEADY

051359

Latest design with locking swivel bracket and large grip handle for comfortable and easy swivelling. Also features a large flat load bearing foot ideal for soft ground. Large foot locks away and silencer pads reduce noise caused by vibration. Hex drive and zinc finish.

#### SPECIFICATIONS

- 750mm open length
- Zinc finish

# COUPLINGS



**COUPLING FIXED PRESSED METAL AL-KO AK7**  
006276

Zinc plated, 760kg max load.

**COUPLING ELECTRICAL AL-KO ZINC PLATED**  
006280

Suits electric brakes. Quick release, 4 hole bolt on, 3500kg max load. 50mm Ball

**SPECIFICATIONS**

- Capacity: 3500kg
- Mounting holes: 4 at 182.5mm x 55mm centres
- Zinc plated

**VERRIDE COUPLINGS**

**006281 COUPLING HYDRAULIC OVERRIDE AL-KO WITH  
HANDBRAKE & 3/4" MASTER CYLINDER MAX  
LOAD 2000KG**

AL-KO Hydraulic override coupling with 2000kg capacity. Includes brake master cylinder and brake handle.

**SPECIFICATIONS**

- 2000kg capacity

**006285 COUPLING MECHANICAL OVERRIDE AL-KO  
ZINC PLATED, MAX LOAD 2 TONNE, NO HAND  
BRAKE, ARM ATTACHMENT**

AL-KO Mechanical override coupling 2000kg, NO brake lever. Four bolt holes.

**FEATURES**

- Holes are 55mm centres apart, across the coupling
- Holes are 185mm centre to centre from front to rear
- Handbrake handle is a separate part and is not included

**SPECIFICATIONS**

- Has a capacity of 2000kg
- Zinc plated



**COUPLING**

**006278 COUPLING QUICK RELEASE AL-KO ZINC PLATED, BOLT ON, 2 HOLE, 2000KG MAX LOAD, HEAD ADJUSTING SCREW**

AL-KO two hole bolt on coupling. Suit trailers without brakes. The bolt holes are in line.

**036199 COUPLING QUICK RELEASE BOLT ON, 3 HOLE, 2270KG MAX LOAD, HEAD ADJUSTING SCREW**

**006302 COUPLING 4WD FIXED 3PCE TRIGG, OFF ROAD, FULL 360 DEGREE ROTATION, TOWBAR ADAPTOR, POLYBLOCK WITH BRASS BUSHES AND 10MM PIN**



**COUPLING SPARE PARTS**

- 006293 PIN COMPLETE T/S TREG COUPLING WITH SPRING AND LYNCH PIN
- 006294 COUPLING LYNCH PIN CLIP TREG SIZE 6MM
- 006312 REVERSING LATCH TRIGG
- 006315 HANDBRAKE PLATE SUIT TRIGG COUPLING
- 036221 COUPLING REVERSING CATCH AL-KO
- 006322 COUPLING PARTS KIT AL-KO - HANDLE, TRIGGER, SPRINGS, SPINDLE
- 006323 COUPLING TRIGGER AL-KO
- 006327 COUPLING ADJUSTABLE SCREW AND NUT KIT AL-KO
- 006332 COUPLING TRIGGER SPRING AL-KO

- 034823 POLY BLOCK TOWBAR ADAPTOR TRIGG
- 036216 DETACHABLE PIN ASSEMBLY TRIGG
- 041490 COUPLING LOCK RING AL-KO SUIT AKS2000 OFFROAD COUPLING
- 050148 COUPLING OFF ROAD LOCK RING
- 006307 TRIGG SAFETY LOCKING CATCH



**036493 VIN PLATE TRAILER I.D. 1 PIECE**

MANUFACTURER		VIN	
DATE OF MANUFACTURE	_____	1	THE SUM OF THE LOAD CARRYING CAPACITIES OF THE TYRES FITTED TO ANY AXLE OR AXLE GROUP OF THE VEHICLE SHALL NOT BE LESS THAN THE RELEVANT LOAD RATING.
GROSS TRAILER MASS	kg _____	2	THE TYRES FITTED TO THIS VEHICLE SHALL HAVE A SPEED CATEGORY AT LEAST EQUAL TO THE RECOMMENDED MAXIMUM VEHICLE OPERATING SPEED.
AGGREGATE TRAILER MASS	kg _____	3	THIS TRAILER WAS MANUFACTURED TO COMPLY WITH THE APPLICABLE AUSTRALIAN DESIGN RULES.
TYRE SIZE/PLY	_____		
NEW PROFILE	_____		
RECORD. COULD TYRE PRESS	kPa _____		
LOAD CARRYING CAPACITY OF			
AXLE OR AXLE GROUP	FRONT _____		
	REAR _____		

- 036226 VIN PLATE TRAILER I.D. PLATE (2 PIECES)
- 039997 COUPLING MOUNT BOLTS SET OF 3 (1 1/2" X 1/2")
- 039998 COUPLING MOUNT BOLTS SET OF 4 (4" X 1/2")



**DO35 COUPLING V3-R**

**044634**

The V3-R version of the DO35 is without a handbrake and ideal for caravans with a preexisting handbrake mounted elsewhere on the A-frame.

**SPECIFICATIONS**

- Articulation: 360 degrees axial, minimum 70 degrees other axes
- Locking: Fully ADR 62/02 compliant including automatic secondary lock
- Finish: Supa Alloy 5
- Bolt pattern: 4 bolts at 185mm x 54mm
- Rating: 3.5 Tonne
- Action: Drop-On
- Maintenance: Fully Greasable

**DO35 COUPLING SPARE PARTS**

**044640 DO35 TOW PIN WF KIT**

**044641 DUST CAP C/W LANYARD**

**044642 DUST CAP C/W LANYARD**

**044643 WDH HR 550/750 - ADAPTOR**



**DO35 COUPLING V3-I WITH INTEGRATED  
HANDBRAKE**

**044635**

Forged steel, high quality polyurethane, laser cut stainless steel and precision casting has been brought together to increase the couplings strength yet also reduce weight. This updated DO35 is over 50% stronger than the outgoing model. These advanced processes have also allowed the elimination of hitch adaptors allowing you to get on the road with less fuss.

**SPECIFICATIONS**

- Articulation: 360 degrees axial, minimum 70 degrees other axes.
- Locking: Fully ADR 62/02 compliant including automatic secondary lock
- Finish: Supa Alloy 5
- Bolt pattern: 4 bolts at 185mm x 54mm
- Rating: 3.5 Tonne
- Action: Drop-On
- Maintenance: Fully Greasable



**MECH BRAKE ARM ATTACHMENT AL-KO**

**044568**

This AL-KO Lever Hand Brake and Mounting Plate suits the AL-KO Mechanical Override Coupling System.

New design means the handle is less likely to foul rear opening vehicle doors



**MECHANICAL PARKING MECHANISM AL-KO**

**036218**

AL-KO top mounting parking lever for mechanical/ Electric trailer/caravan brakes. Has an easy to use press button release. Note: This does not mount directly with 4 hole couplings - but it can be mounted to A-Frame or similar.



**COUPLING HYDRAULIC BRACKET WITH  
MASTER CYLINDER**

**006317**

AL-KO Hydraulic Conversion With 3/4 inch cylinder. Used to convert a AL-KO Mechanical coupling for use with hydraulic brakes.



**TREG BLOCK COUPLING AND ACCESSORIES**

**006301 COUPLING TREG POLYBLOCK WELD ON, MAX LOAD 3000KG, NO HAND BRAKE (WELD ON WITH 3/4 PIN)**

Treg is the original off-road polyblock coupling, and if you're fair dinkum about going off road with your trailer this is the coupling for you!

**FEATURES**

- Coupling body rotates 360 degrees
- Because of it's design the Treg Off Road Coupling allows a huge departure angle with a 70 degrees vertical oscillation angle allowing it to go places where standard couplings would fail.
- No special fitting required just remove your standard tow ball and put the Treg yoke into your standard tow bar tongue and you're away.
- TRIGG handbrake assembly suits this coupling (Not included).

**SPECIFICATIONS**

- 1 x Treg Poly Block Trailer Coupling
- 1 x Treg Yoke to suit Towing Vehicle
- Bolt on type

**006295 COUPLING U BRACKET AND SPRING PIN TREG DETACHABLE**

Treg Detachable U Bracket & Pin.

**SPECIFICATIONS**

- 3000kg
- Pin 3/4 inch
- Thread 3/4 x 2 1/2 inch

**006293 TREG COUPLING SPRING/PIN/AND LYNCH PIN KIT**

This pin is a direct replacement for the Treg coupling.

**SPECIFICATIONS**

- 3/4 Inch (19mm) Diameter Pin
- 180mm in Length
- Lynch Pin 1/4 Inch (6mm)
- Zinc Yellow Finish



## COUPLING

- 05 1090 ARK OFF ROAD COUPLING ELEC.
- 05 1093 ARK OFF ROAD COUPLING O/R BRAKE
- 05 1094 ARK OFF ROAD COUPLING ELEC. W/RATCHET
- 05 1350 ARK QUICK RELEASE COUPLING
- 05 1352 ARK XO SERIES COUPLING ELEC 3.5T
- 05 1354 ARK OVER RIDE COUPLING ZINC
- 05 1355 ARK OVER RIDE COUPLING GAL.
- 05 1357 ARK ELECTRIC COUPLING ZINC
- 05 1364 ARK OVER RIDE COUPLING
- 05 1367 ARK XO SERIES COUPLING 2T O/R
- 050141 COUPLING PLUNGER TYPE TRIGGER



## OFFROAD COUPLING PARK LEVER

050176

Handbrake lever to suit AL-KO offroad coupling 044408.

### SPECIFICATIONS

- ALKO Parking Brake arm, mounts under the 4 bolt hole couplings and the ratchet arm catches on the coupling
- Holes are 55mm and 185mm apart
- Low Profile – 140mm from the top of the plate to the bottom of the handle



## AL-KO BRAKE COUPLING

044408

Engineered by AL-KO in Australia specifically for extreme off-road adventure, the new AL-KO Off-Road Ball Coupling incorporates extreme vertical and horizontal articulation as well as a quick & easy hitching design that requires no pin or hole alignment.

It's made from high quality materials designed to endure serious off road use and provide you with the confidence you need to take your rig in to even the most remote parts of Australia.

The new & improved range of low profile Off-Road Ball Couplings are suitable for use with a standard 50mm ball.



## AL-KO PARKBRAKE

044409

Suits mech o/ride coupling rear holes.

\*May require spacer plate for coupling front holes.



## PINTLE HOOK

050399

Pintle hook 10 tonne.

### SPECIFICATIONS

- Hook Capacity: 6000 kg
- Ball Capacity: N/A
- Mounting Pattern: 45mm x 85mm
- Hole Diameter: 12.5mm
- Surface Finish: Painted



## BRAKE SPARE PARTS

- 006361 BRAKE CABLE ADJUSTER WITH PULLEY
- 006362 BRAKE CABLE PULLEY
- 006370 BRAKE CABLE KIT (8M+ADJ+2CLIPS+2PULLEYS)
- 006372 WIRE CABLE CLAMP ONLY 5MM GAL
- 006375 CABLE SWAGE 2.5MM
- 036194 WIRE CABLE CLAMP ONLY 4MM
- 006346 HYDRAULIC MASTER CYLINDER 3/4"
- 006350 HYDRAULIC MASTER CYLINDER CAP ONLY SUIT 3/4"



## MASTER CYLINDER CAP 3/4

050110



## BRAKE CABLE ADJUSTER SKIN PACK

050146

### SPECIFICATIONS

- From slipper springs to tow ball mounts
- All quality materials at a great price
- Easy to install and quality for life



## UTILITY LYNCH PIN TRACTOR CLIP B3

035385

### SPECIFICATIONS

- 8mm
- 38mm diameter of ring



# SPRINGS



## LEAF SPRING - EYE TO EYE SHACKLE (CAPACITY LISTED FOR 2 SPRINGS)

- 036299 45 X 8 X 710 3 LEAF 850KG
- 036300 45 X 8 X 710 4 LEAF 1100KG
- 036301 45 X 8 X 710 5 LEAF 1300KG
- 036302 45 X 8 X 710 6 LEAF 1500KG
- 040754 45X8X840 7 LEAF 1600KG



## SLIPPER SPRING (CAPACITY LISTED FOR 2 SPRINGS)

- 036328 45 X 6 610 7 LEAF 1350KG
- 036333 DACROMET 3 LEAF 600KG
- 036334 DACROMET 4 LEAF 750KG
- 036335 DACROMET 5 LEAF 1000KG
- 036336 DACROMET 6 LEAF 1200KG
- 036337 DACROMET 7 LEAF 1350KG
- 051563 DACROMET 9 LEAF 1600KG
- 040757 44 X 6 X 720 6 LEAF 1050KG
- 040758 44 X 6 X 720 5 LEAF 900KG



## TANDEM 45 X 8 X 710 8 LEAF

036309

Offset centre pin to suit rocker tandem axle setups.

### SPECIFICATIONS

- 975kg



## SPRING KIT AND SPARE PARTS

### 036364 FRONT U HANGER WITH 12MM HOLE 45MM WIDE

Front U Hanger With 12mm Hole. Suit 45mm springs. These are used the front of either slipper or 2 eye springs. They accept a 12mm or 1/2 Inch bolt x 3 1/2 Inch. Bolt and nut are NOT included.

### 036365 FRONT U HANGER WITH 14MM HOLE 45MM WIDE

Front U Hanger With 14mm Hole, suit 45mm springs. These are used the front of either slipper or 2 eye springs. They accept a 14mm or 9/16 Inch bolts x 3 1/2 Inch. Bolt and nut are NOT included.

### 036367 REAR HANGER BLOCK NO BUSH, 22MM I.D.

Rear Hanger Block. These will accept a bush (NOT INCLUDED) 7/8 inch (22mm) outside diameter and 1 3/4 inch (45mm) long. The inside diameter of bush ordered should be 1/2 inch or 9/16 to suit bolts used.

### SPECIFICATIONS

- Suit 45mm wide spring
- Requires bush with outside dia. of 7/8 inch

### 036368 REAR U HANGER SUIT SLIPPER SPRING

Rear Hanger Suit Slipper. These are used only for rear of slipper springs.

## NYLON BUSH

- 044148 NYLON BUSH 1 3/4 X 3/4 X 1/2IN
- 044149 NYLON BUSH 1 3/4 X 7/8 X 1/2IN
- 044150 NYLON BUSH 1 3/4 X 7/8 X 9/16IN

### 036386 NYLON BUSH 60MM X 7/8 X 5/8IN

### SPECIFICATIONS

- Length 60mm
- Outside diameter 7/8 inch
- Inside diameter 5/8 inch

### 006535 NYLON BUSH 1 3/4 X 9/16 X 3/4IN"

### SPECIFICATIONS

- Length 1 3/4 inches
- Outside diameter 3/4 inch
- Inside diameter 9/16 inch

### 036378 SHACKLE PLATE GALVANISED, 1/2" HOLES, 65MM CENTRE TO CENTRE

### 006526 SHACKLE PLATE 9/16" HOLES, 75MM CENTRE TO CENTRE

### 038532 SHACKLE PLATE AL-KO BLACK, M16 S/60MM WIDE SPRINGS

### 036379 SHACKLE PLATE GALVANISED, 9/16" HOLES, 75MM CENTRE TO CENTRE

2 shackles are required for each spring.

### 038810 SHACKLE BOLT AL-KO GREASEABLE, M16 (S/60MM WIDE SPRINGS NYLOC NOT INCLUDED)

### 038133 CENTRE ROCKER PIN AL-KO M18 (NYLOC NOT INCLUDED)

### 036375 SHACKLE BOLT 3 AND 1/2" X 1/2" WHIT

Bolt only 3 1/2 X 1/2 Whitworth. Suit 45mm wide spring assemblies with 12mm holes. Most slipper springs take this bolt in the front eye.

### 036369 SHACKLE BOLT AND NUT 3 1/2"X9/16" GREASEABLE

Shackle Bolt & Nut, 3 & 1/2 X 9/16, Greaseable, suit 9/16 hole. These come with a Nyloc nut. Suit 45mm springs. Hollow with internal thread to suit grease nipple (nipple not included)

### 036370 SHACKLE BOLT AND NUT 3 1/2"X5/8" GREASEABLE

Shackle Bolt & Nut, 3 & 1/2 X 5/8, Greaseable. Hollow with internal thread to suit grease nipple (nipple not included). Suit 45mm spring with 5/8 Inch hole in bush.

### 036371 SHACKLE BOLT AND NUT 3 1/2"X9/16" NON-GREASE

Shackle Bolt & Nut, 3 1/2 X 9/16. These are non-greaseable, suit 9/16 hole and 45mm springs.

### 006527 FISH PLATE MULTI FIT 8MM BLACK

### 036380 FISH PLATE GALVANISED, MULTI FIT 8MM

Fish Plate (Multi-Fit) 8mm, Galvanised. Fits 40mm and 45mm axles and 45mm wide springs. Available as Galvanised or Black steel. These are usually placed below the leaf spring, with the u-bolts thread pointing down.

### 036387 AXLE PAD SUIT FLAT AXLE

Axle Pad Suit Flat Axle. Fits between axle and spring. It is centred over the bolt that holds the spring together.

### 036376 GREASE NIPPLE STRAIGHT

Grease Nipple Straight. These fit the greaseable shackle bolts

### 038809 NUT NYLOC M16 AL-KO

### 038135 NUT NYLOC M18 AL-KO

### 006530 NUT NYLOC 1/2" WHIT

### 006531 NUT ZINC PLATE 1/2" WHIT



## U BOLTS

The U-Bolts come as either Square ended or Round ended to suit the axle shape.

The length is shown in mm as the first number in the product title.

They come as 40mm, 45mm or 50mm plus some other widths - the width is shown as the second number in the title.

These are all 1/2 whitworth thread, and you must order nuts as separate items. Either 2 nyloc nuts per u-bolt or 4 standard nuts per u-bolt.

Sold each.

**036408 ZINC SQUARE 115MM X 40MM 1/2" WHITWORTH SQUARE**

**036410 ZINC SQUARE 125MM X 45MM 1/2" WHITWORTH SQUARE**

**036413 ZINC SQUARE 140MM X 45MM 1/2" WHITWORTH SQUARE**

**036414 ZINC SQUARE 150MM X 40MM 1/2" WHITWORTH SQUARE**

**036416 ZINC SQUARE 165MM X 45MM 1/2" WHITWORTH SQUARE**

**036417 ZINC RND 100MM X 40MM 1/2" WHITWORTH ROUND**

**036418 ZINC RND 125MM X 40MM 1/2" WHITWORTH ROUND**

**036420 ZINC RND 125MM X 50MM 1/2" WHITWORTH ROUND**



## SHOCK ABSORBERS

### 036423 SHOCK ABSORBER KIT - AL-KO

AL-KO, Caravan Shock absorbers, Pair When extended, they are 380mm from centre of top bolt, to centre of lower bolt. They will close down to 250mm, centre to centre.

#### SPECIFICATIONS

- 2 Shock absorbers
- Left and Right lower mounting bracket (bolt to Spring U-Bolt)
- 2 Upper mounting brackets
- Rated at 1300kg per pair
- Mounting holes in lower bracket are 75mm between centres



## FLAT WASHER 1/2IN ZINC PLATED

040006

Suitable for spring and axle U-Bolts.



## SPRING ROLLER

043964

Suits rocker/roller tandem spring sets.



## UBOLT GAL SQ

050300 75MM X 50MM

050301 60MM X 75MM

050302 100MM X 75MM

050303 100MM X 50MM

050304 125MM X 50MM

050305 125MM X 100MM

Sold in pairs.



## GALVANISED U BOLTS WITH NYLOC NUTS

042592 U-BOLT GALVANISED 39MM ROUND

042593 U-BOLT GALVANISED 40MM SQUARE

042594 U-BOLT GALVANISED 45MM SQUARE

Sold each. Includes galvanised nylon nuts.

# VEHICLE STEPS



## STEP SINGLE TREAD 455X170MM

**006501**

Single low profile steel step. Used under caravan

### SPECIFICATIONS

- Steel 505mm wide
- 180mm deep mounting frame
- Extends 65mm

## SPARE PARTS

CODE	PRODUCT NAME
<b>006510</b>	ELECTRIC STEP MAIN SWITCH ONLY
<b>040912</b>	ELECTRIC STEP STANDARD HARNESS LOOM 1300MM LOOM SUIT SINGLE STEP
<b>039820</b>	STEP TENSION SPRINGS PAIR SUITS TECHNO STEPS
<b>036780</b>	ELECTRIC STEP SIDE MOULD GREY PLASTIC SUITS ELECTRIC STEPS
<b>043707</b>	MOTOR ONLY (LEFT SIDE) SUIT 006508 AND 006509

# CARAVAN MOVERS



## CARAVAN MOVER ELITE® 2 043321

### FEATURES

- Economical and effective solution for maneuvering your caravan
- Aluminium rollers that are friendly to tyres
- Optimum compact design, reasonable ground clearance, suitable for almost any light duty single axle chassis
- Corrosion-protected by e-coating and powder coating
- Easy winding action to engage or disengage the roller
- The powerful motor will not allow the RV to roll while being maneuvered on a gradient (Do not use the system as a brake. Always disengage rollers when not in use)
- Caravan/trailer stops immediately and automatically if it is out of range of the remote control or there is malfunction
- Not submersible

### SPECIFICATIONS

- Model Elite® 2 Em303
- Part Number 043321
- Operational Voltage 12v Dc
- Average Current Consumption 20 Amps
- Maximum Current Consumption 100 Amps
- Remote Control
- Transmitting Frequency 868 Mhz
- Speed 90mm / Sec.
- Weight 37kg Approx.
- Safe Working Load (Swl) 1,800kg (2 Motors) Or Up To 1,500kg On An 18% Gradient 2,500kg (4 Motors) Or Up To 1,800kg On An 18% Gradient
- Minimum Width (Caravan/Trailer) 1800mm
- Maximum Width (Caravan/Trailer) 2500mm
- Maximum Tyre Width 205mm



## CAMEC CARAVAN MOVER ELITE PRO2 043322

### FEATURES

- Accurate and durable gearing
- Aluminium rollers that are friendly to tyres
- Simply by pressing the button on remote control handset the rollers will properly engage or disengage on the tyres
- Manoeuvre your caravan effortlessly with soft stop and start
- The powerful motor will not allow the RV to roll while being maneuvered on a gradient (Do not use the system as a brake. Always disengage rollers when not in use)
- Caravan/trailer stops immediately and automatically if it is out of range of the remote control or there is malfunction
- If you forget to disengage the rollers, an emergency function will wind them back if it is connected to a tow vehicle
- Not submersible

### SPECIFICATIONS

- Model Elite® Pro 2 Em305
- Part Number 043322
- Operational Voltage 12v Dc
- Average Current Consumption 30 Amps
- Maximum Current Consumption 120 Amps
- Remote Control
- Transmitting Frequency 868 Mhz
- Speed 110mm / Sec
- Weight 33kg Approx.
- Safe Working Load (Swl) 2,000kg (2 Motors) Or Up To 1,750kg On An 18% Gradient 3,000kg (4 Motors) - Up To 2,350kg On An 18% Gradient
- Minimum Width (Caravan/Trailer) 1800mm
- Maximum Width (Caravan/Trailer) 2500mm
- Maximum Tyre Width 205mm



## TRAILER VALET MOVER 042965

Manual mover designed for trailers up to 2,200kg with a ball weight of up to 220kg. Perfect for small caravans, campers and car trailers. Very simple to use.

### FEATURES

- Attaches to your A-frame and can replace your jockey wheel
- Patented drive system with high and low drive gears (select high or low gear depending on your terrain)
- Brake is incorporated in the system for safety
- Unit can be rotated out of the way on the mount for travel or removed completely
- Spare mounting plates are available to enable you to move the Trailer Valet from one vehicle to another easily

### SPECIFICATIONS

- Weight: 20.5kg
- High quality steel with powder-coated hammer finish
- 2 x 9" pneumatic tyres



## TRAILER VALET XL MOVER 043705

The Trailer Valet XL is the toughest and most compact trailer dolly. Sharing the same great features as its little brother, but with a few upgrades. The XL moves most trailers up to 4,500kg just using a crank handle or an 18V drill. It features dual, 9" tyres that can handle a ball weight of up to 400kg and positraction technology for making tight turns. The automatic brake engages when the handle is released for superior safety, making it ideal for large caravans, boats, construction and farm equipment, horse floats and flat bed trailers.

### FEATURES

- Handles most trailers weighing up to 4,500kg (450kg tongue weight)
- Patented ball attachment mechanism for quick attachment and greater maneuverability
- High strength pneumatic tyres that can withstand 225kg of pressure per tyre
- A greater gear reduction to make cranking even easier
- High quality steel with powdercoat hammer finish
- Brass bearings
- Drill attachment that enables the user to attach most 18V cordless drills
- Automatic safety brake
- One year manufacturer's warranty
- Positraction for maximum traction and ease of handling

### SPECIFICATIONS

- Tow ball coupling ball size: 50mm
- Weight: 23.5kg

## SPARE PARTS

CODE	PRODUCT NAME
044870	DISTANCE PLATES FOR ELITE PRO 2
043677	CONTROL BOX SERIES 2 ELECTRONICS FOR ELITE PRO
042624	REMOTE HANDSET FOR CAMEC ELITE MOVER
042633	REMOTE HANDSET FOR CAMEC ELITE PRO MOVER
043498	MAINFRAME COVER ELITE
042628	ISOLATION KEY FOR CAMEC ELITE AND ELITE PRO
042632	MOTOR RUBBER COVER IN PAIR
043672	COVER A DECORATION FOR ELITE
043673	COVER B DECORATION FOR ELITE

## SPARE PARTS

CODE	PRODUCT NAME
042966	TRAILER VALET MOUNT CLAMP
042967	TRAILER VALET TYRE AND TUBE 2X9"
042968	TRAILER VALET CRANK HANDLE
042969	TRAILER VALET BRAKE CAP HANDLE
043706	TRAILER VALET DRILL ATTACHMENT
050998	TRAILER VALET 1 7/8" BALL